



WHICH LUBE TO CHOOSE?

SSC carries a wide variety of industrial lubricants to help quiet doors, inhibit rust and dissolve grease and grime, offering long-lasting protection.

| SSC Part # | Name | Lube Type | Ounces/Per Can | California Compliant | Private Label Available | Food Grade | Temp Range (F) | Purpose |
|------------|--------------------------|---------------|----------------|----------------------|-------------------------|------------|----------------|---|
| SSC123 | 3-Way Nozzle Spray Lube | PTFE | 13 | ✓ | NO | NO | N/A | All purpose lubricant with a 3-way adjustable nozzle that allows control of flow from mist to stream. Prevents rust and corrosion build up while not attracting dust or dirt over time. |
| 434 | Multi-Purpose Spray Lube | White Lithium | 14 | NO | ✓ | NO | -60 / 350 | Designed to reduce metal to metal friction on any surface under heavy loads. Formulated with rust corrosion inhibitors and waterproofs the treated surface. |
| 438C | Multi-Purpose Spray Lube | White Lithium | 6 | NO | ✓ | NO | -60 / 350 | Designed to reduce metal to metal friction on any surface under heavy loads. Formulated with rust corrosion inhibitors and waterproofs the treated surface. |
| 560129 | Multi-Purpose Spray Lube | White Lithium | 14 | ✓ | ✓ | NO | -60 / 350 | Designed to reduce metal to metal friction on any surface under heavy loads. Formulated with rust corrosion inhibitors and waterproofs the treated surface. |
| 449 | Ultra Gel Spray Lube | PTFE | 13 | ✓ | ✓ | NO | -30 / 600 | A high adhesive strength lubricant that withstands extreme pressure. Easily dispensed spray penetrates tight areas by initially going on thin and immediately forming a viscous film. |
| 492845 | Z-45 Spray Lube | Oil | 15 | NO | ✓ | NO | -55 / 475 | Penetrating lubricant that contains PTFE for added lubricity during extreme temperatures. Defends against corrosion and dissolves grease and grime. |
| 464 | Silicone Spray Lube | Silicone | 9.75 | ✓ | NO | NO | -58 / 600 | Non-drying formula lubricates, protects and lengthens life of all rubber parts. Thick viscous film adheres to most surfaces like a magnet. |

LUBE COMPARISON SHEET

| SSC Part # | Name | Lube Type | Ounces/Per Can | California Compliant | Private Label Available | Food Grade | Temp Range (F) | Purpose |
|-------------------|---------------------|-----------|----------------|----------------------|-------------------------|------------|----------------|---|
| 1STAYDLUBE | 1st Ayd Spray Lube | PTFE | 13 | ✓ | NO | NO | N/A | A transparent high pressure, water resistant lubricant that penetrates tight areas and sets up into a grease-like gel with high adhesive strength. Fortified with PTFE, it dries clear and is virtually invisible once applied. |
| GS11A | Getsome Spray Lube | Oil | 11 | ✓ | NO | ✓ | 0 / 360 | Long lasting, non toxic, no odor, non staining, non conductive, non halogenic, non carcinogenic, LOW VOC, NO CFCs, and safe on plastics, metals, enamels, etc. Professional and commercial grade. Food Grade H-1NSF certified. |
| SLIPIT | Slip-It Spray Lube | Silicone | 11 | ✓ | NO | ✓ | 220 | Ideal for use in hard to reach spots and inhibits rust and corrosion. Dielectric properties for use in electrical applications. |
| 463 | Foamy Spray Lube | Oil | 15.75 | ✓ | NO | NO | N/A | Foaming action provides extended penetration and moisture displacement. The foam minimizes run off and keeps the product working on rusted parts. |
| PROSL | PRO SL Spray Grease | Synthetic | 9 | ✓ | NO | NO | -65 / 300 | Synthetic penetrating lubricant with excellent rust-inhibitive properties. When applied correctly, it can provide years of corrosion protection in fresh water environments. |
| 436 | PRO 21 Spray Grease | Synthetic | 9 | ✓ | NO | NO | -80 / 400 | Formulated with a superior base stock and advanced additives which will lubricate and protect machinery, parts, and surfaces against friction, oxidation, corrosion, and other types of distress. |
| 135063 | Chain & Cable Fluid | Oil | 11 | ✓ | NO | NO | -40 / 350 | Lubricating, penetrating, and cleansing fluid designed to penetrate strands and reduce friction between wire rope, while protecting inner core from rust and corrosion. |



SERVICE SPRING CORP.
1703 TOLLGATE DR.
MAUMEE, OH 43537

800.752.8522 | SERVICESPRING.COM